

LED-CORNER

aluminium | 4000 K | 180 led/m | 1080 lm/m | Ra>85
Product code: 682331

A versatile corner profile

LIMENTE LED-CORNER IP44 B is a versatile light fixture suitable for either working light or mood light. The fixture can be used in any space, where the fixture can be placed in a corner. The light is stylish and continuous with no connection points interrupting the light, which provides even light throughout the area.

See "Installation pictures" for tips on how to use LED-CORNER IP44 B in a kitchen workspace but also to provide indirect lighting when placed above upper cabinets, in plinths, in ceilings or inside a wardrobe! LIMENTE LED-CORNER profiles are available in three amazing colors (aluminum, black, white), in multiple lengths (2-6m) and three different color temperatures (3000K, 4000K and 2700K-6000K). The profile itself has a standard length of 2m and can be shortened to a desired length.

[Learn more from our website](#)

Dimming and lighting control


Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cosy by dimming your LIMENTE LED-CORNER with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

[Learn more from our website](#)

Easy installation

LIMENTE LED-CORNER IP44 B is fast and easy to install with the installation tools included.

[Learn more from our website](#)



THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2 m x 2
- end pieces
- fasteners
- led-ribbon 4 m, with driver in both ends
- 3m power cords 2 pcs

COR. 40 COM 4K AL PROF.LIGHT

OVERVIEW

PRODUCT CODE	682331
GTIN-CODE	6438400000575
ELECTRICAL NUMBER	4129648
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	Alulook
LAMP TYPE	LED

SPECIFICATIONS

PRODUCT DIMENSIONS	4000.0 x 19.0 x 19.0
POSITION	To an interspace, On the top cabin, To the vitrine, Inside the cabin, To damp spaces
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 85
RATED LIFE TIME	35.000h (L80B10)
ENERGY EFFICIENCY CLASS	F
LUMINOUS FLUX	1080 lm/m
EFFICIENCY	
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP44
NUMBER OF LEDS/M	180
INPUT POWER	45 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	Top, hole Ø 8 mm
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	12
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_led-corner.pdf

COR. 40 COM 4K AL PROF.LIGHT

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LED POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LED POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LED POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640420	SMART 420, WIRELESS LIGHT CONTROL
640421	SMART 421, WIRELESS LIGHT CONTROL
640422	SMART 422, WIRELESS LIGHT CONTROL
640424	SMART 422, WIRELESS LIGHT CONTROL
640425	SMART 425, WIRELESS LIGHT CONTROL

COR. 40 COM 4K AL PROF.LIGHT

